



**YT – YSER Tack**

*Triethylenoglicol Esters of Stabilized Gum Rosin are specially manufactured to be used as tackifiers in adhesives industry.*

**□ GENERAL SPECIFICATIONS**

	<b>YT 341</b>	<b>YT 342</b>	<b>YT 343</b>	<b>YT 344</b>
<b>Acid Number – Specs</b>	20 max	20 max	20 max	20 max
Acid number – Typical	15	15	15	15
<b>Viscosity @ 20°C ( mPa.s ) – Specs</b>	550.000 ± 50.000	100.000 ± 20.000	40.000 ± 15.000	10.000 ± 3.000
Viscosity @ 20°C ( mPa.s ) – Typical	550.000	100.000	40.000	10.000
<b>Colour Gardner – Specs</b>	5 max	5 max	5 max	5 max
Colour Gardner – Typical	3	3	3	3

**□ SPECIAL REMARK**

*The standard characteristics of the resin, with regards to the Viscosity and Acid Value, can be adapted, under the limits of our specs, to the special requirements of our customers.  
Safety Data Sheet and Technical Data Sheet are available under request for each product.*

**□ CHARACTERISTICS**

*Excellent tack  
Good compatibility with natural and synthetic rubber wax  
Good compatibility with EVA polymers  
Good compatibility with wax  
Total compatibility with aliphatic hydrocarbon resins*

**□ APPLICATIONS**

*Resins specially manufactured to be used as tackifiers in floor coating adhesives, P.S.A. and permanent tack hot - melt adhesives.*

**□ FORM OF SUPPLY**

*200 kg metallic drums  
Road tanks*

The reproduction of this document is completely forbidden

The information in this publication is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. We are, at all times, willing to study customer's specific outlets involving our products in order to enable their most effective use.



***Distributed in the U.S.A. by:***  
***PDM, Inc., 104 Webster Building, 3411 Silverside Road, Wilmington, DE 198104806 • U.S.A.***  
***Toll-Free (800) 288-0768 • Phone (302) 478-0768 • Fax (302) 478-0299 • E-Mail: godon@zdial.com***